OVE Austrian Electrotechnical Association

Eschenbachgasse 9 | 1010 Wien | Austria ZVR: 327279890 | www.ove.at

2 V 1 (: 02 / 2 / 0000 | WW

OVE Certification

Kahlenberger Str. 2A | 1190 Wien | Austria T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at



Page 1 of 6

ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark



Certificate No.: 43-151-17 Valid from: 2024 02 25

until: 2026 02 25

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Certificate holder: PC Electric Ges.m.b.H.

Diesseits 145

4973 St. Martin im Innkreis

Austria

Product: Portable socket-outlets for industrial purposes

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the certificate holder holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s).: 3722-1861/23

Österreichischer Verband für Elektrotechnik

Head of OVE Certification

Digitally signed by T. Neumayer Email=t.neumayer@ove.at

Dipl.-Ing. T. Neumayer

OVE

Wien, 2024 01 08







Certificate No.: 43-151-17 Date: 2024 01 08

Page 2 of 6

Manufacturer:

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Factory location(s):

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01 ÖVE/ÖNORM EN 60309-2:2013-03-01 OVE EN IEC 60309-1:2023-07-01 OVE EN IEC 60309-2:2023-07-01 IEC 60309-1:2021 IEC 60309-2:2021

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

Product: Portable socket-outlets for industrial purposes

Type designation: Rating:	Trademark:
2335 Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 see typelist	PCE / ELCEE / SIROX / METECEE
2336 Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 see typelist	PCE / ELCEE / SIROX / METECEE
2345 Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67	PCE / ELCEE / SIROX / METECEE



see typelist





Certificate No.: 43-151-17

Date: 2024 01 08 Page 3 of 6

2346 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 see typelist

2355 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 see typelist

2356 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 see typelist

233 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 67 or IP 66/IP 67 see typelist

234 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 67 or IP 66/IP 67 see typelist

235 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 67 or IP 66/IP 67 see typelist

23351 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 see typelist

23361 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 see typelist

23451 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 see typelist

OVE Certification





Certificate No.: 43-151-17

Date: 2024 01 08 Page 4 of 6

23461 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 see typelist

23551 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 see typelist

23561 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 see typelist

2331 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 2P+PE IP 44 see typelist

2341 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+PE IP 44 see typelist

2351 PCE / ELCEE / SIROX / METECEE

Rated current: 63 A 3P+N+PE IP 44 see typelist





Certificate No.: 43-151-17 Date: 2024 01 08

Page 5 of 6

_	_			4		_			-	1			1		
2	3	5	5	1	-	6	C	q	*	V	<u> </u>	m			
													Lid axis	3	
													blank	made of PC/ABS	
													m	made of brass (nickel-plated)	
													0 1 1		
										L			Contact		
													blank v	uncoated contacts nickel plated contacts	
													V	Thicker plated contacts	
													Colour		
													blank	standard type	
													*	reserved for additional colours	
													Housing	~	
													blank	g Design 1	
													cq	Design 2	
														-	
													Clock p	osition earthing contact	
													1	1 h	
													2	2 h	
													3	3 h	
													4	4 h	
													5	5 h	
													7	6 h 7 h	
													8	8 h (not available in 4- and 5-poles)	
													9	9 h	
													10	10 h	
													11	11 h	
													12	12 h	
													Customer type		
													- Trademark PCE		
													Degree of protection		
													blank	IP67 or IP66/IP67	
													1	IP44	
													Dilatas	water of	
			L										Pilot co blank	without pilot contact	
													5	with pilot contact	
													6	with PCS system	
													Dalaa		
													Poles 3	3-poles	
													4	4-poles	
													5	5-poles	
													Rated c		
													3	63A	
													Ground		
													2	portable socket-outlet	

OVE Certification





Certificate No.: 43-151-17

Date: 2024 01 08 Page 6 of 6

Typelist

Туре	Rated current	Earthing contact pos.	Rated operating voltage V	Frequency Hz	Insulation voltage
	Α	h	Other ratings	Other ratings	V 500*), 690
		2	>50	>300 - 500	500*), 690
		3	>50 – 250	DC	500*), 690
233		4	100 – 130	50 and 60	500*), 690
2335	63	6	200 – 250	50 and 60	500*), 690
2336*)		7	480 – 500	50 and 60	500*), 690
2331	03	8**)	>250	DC	500*), 690
23351		9	380 – 415	50 and 60	500*), 690
23361*)		10	>50 - 413	>100 - 300	500*), 690
		12	Supply from an	50 and 60	500*), 690
		12	isolating transformer	50 and 60	500), 690
		1	Other ratings	Other ratings	500*), 690
		2	>50	>300 - 500	500*), 690
		3	380	50	500*), 690
		3	440	60	300), 090
234		4	100 – 130	50 and 60	500*), 690
2345		5	600 – 690	50 and 60	690
2346*)	63	6	380 – 415	50 and 60	500*), 690
2341	00	7	480 - 500	50 and 60	500*), 690
23451		9	200 – 250	50 and 60	500*), 690
23461*)		10	>50	>100 - 300	500*), 690
		11	440 – 460	60	500*), 690
		12	Supply from an	50 and 60	500*), 690
		12	isolating transformer	00 4114 00	000), 000
		1	Other ratings	Other ratings	500*), 690
		2	>50	>300 - 500	500*), 690
		3	220/380	50	500*), 690
			250/440	60	,,
235		4	57/100 – 75/130	50 and 60	500*), 690
2355		5	347/600 – 400/690	50 and 60	690
2356*)	63	6	200/346 – 240/415	50 and 60	500*), 690
2351		7	277/480 – 288/500	50 and 60	500*), 690
23551		9	120/208 – 144/250	50 and 60	500*), 690
23561*)		10	>50	>100 - 300	500*), 690
		11	250/440 – 265/460	60	500*), 690
		12	Supply from an	50 and 60	500*), 690
			isolating transformer		,, ,

^{*)} Types 2336, 23361, 2346, 23461, 2356, 23561 with insulation voltage 500 V and with add. marking: "Only for use with electrical interlock"





^{**)} Earthing contact position 8h > 250V DC only for types 2335, 23351, 2336, 23361 with add marking: "Only for use with electrical interlock"